

WHAT IS CLAIMED IS:

1. A printed circuit board wiring configuration check system for checking a wiring configuration which is tentatively designed on a printed circuit board,

5 comprising:

an object determination unit for determining if there exists a high speed signal wiring as a result of evaluation using a predefined equation which contains at least a part of circuit information of said printed circuit board as a variable, said determination being executed after extracting a pair of a driver and a receiver sequentially from a group of components existing on said wiring, and after extracting circuit information of said driver corresponding to one of said pair;

10 a segment extraction unit for extracting a segment that is nearest to said board edge from a group of segments each defining a set of a minimum unit of a wiring configuration for said wiring;

15 a plane edge specifying unit for specifying a plane edge that is nearest, in a perpendicular direction, to a wiring between a driver and a receiver in said segment as a result of a survey of the wiring configuration of said segment extracted;

20 a unit for determining a perpendicular distance between the wiring extending from the driver to the receiver of said segment and said plane edge;

25 a unit for computing a minimum interlayer distance required between a wiring layer of said segment and a layer of said plane on the basis of a pattern and a circuit design specification on the wiring configuration of the extracted segment;

30

09872955-060101

a distance determination unit for comparing said perpendicular distance determined and said interlayer distance computed; and

a message display unit for displaying a message that  
5 contains a predetermined instruction corresponding to said wiring in accordance with a result of determination by said distance determination unit.

2. A printed circuit board wiring configuration check  
10 system as claimed in claim 1, further comprising:

a unit for computing a voltage level of a pulse current flowing through said wiring according to said circuit information; and

a second object determination unit for determining a  
15 presence of a high speed signal wiring when said voltage level computed is not lower than a predetermined reference voltage.

3. A printed circuit board wiring configuration check  
20 system as claimed in claim 2, wherein

said unit for computing the voltage level of the pulse current computes a voltage level thereof on the basis of a result of determination of a predetermined conditional equation which contains, as its variable, a  
25 maximum applicable frequency, a rise time, a pulse width and an amplitude that are included in said circuit information.

4. A printed circuit board wiring configuration check  
30 system as claimed in claim 1, wherein

said wiring configuration is classified, as its type, a micro strip line, a single strip line, or a double strip line.

5 5. A printed circuit board wiring configuration check system as claimed in claim 1, further comprising  
a display unit for displaying a message in  
accordance with a result of computation obtained using a  
predetermined mathematical equation which contains at  
10 least a part of said circuit information as its variable.

6. A method for checking a wiring configuration which is tentatively designed on a printed circuit board, comprising the steps of:

15 determining if there exists a high speed signal wiring using circuit information of said printed circuit board, said determination being executed after extracting a pair of a driver and a receiver sequentially from a group of components existing on said wiring, and after  
20 extracting circuit information of said driver corresponding to one of said pair;

extracting a segment that includes said high speed signal wiring and is nearest to said board edge from a group of segments each defining a set of a minimum unit  
25 of a wiring configuration for said wiring;

specifying a plane layer edge that is nearest, in a perpendicular direction, to a wiring between a driver and a receiver in said segment extracted;

determining a perpendicular distance between the  
30 wiring extending from the driver to the receiver of said segment and said plane layer edge;

computing a minimum interlayer distance required between a wiring layer of said segment extracted and said plane layer;

5 comparing said perpendicular distance determined and said interlayer distance computed; and

displaying a message that contains a predetermined instruction corresponding to said wiring in accordance with a result of said comparison.

10 7. A computer program for causing a computer to check a wiring configuration which is tentatively designed on a printed circuit board, comprising the steps of:

15 determining if there exists a high speed signal wiring using circuit information of said printed circuit board, said determination being executed after extracting a pair of a driver and a receiver sequentially from a group of components existing on said wiring, and after extracting circuit information of said driver corresponding to one of said pair;

20 extracting a segment that includes said high speed signal wiring and is nearest to said board edge from a group of segments each defining a set of a minimum unit of a wiring configuration for said wiring;

25 specifying a plane layer edge that is nearest, in a perpendicular direction, to a wiring between a driver and a receiver in said segment extracted;

determining a perpendicular distance between the wiring extending from the driver to the receiver of said segment and said plane layer edge;

09872955, 060101

computing a minimum interlayer distance required  
between a wiring layer of said segment extracted and said  
plane layer;

5 comparing said perpendicular distance determined and  
said interlayer distance computed; and

displaying a message that contains a predetermined  
instruction corresponding to said wiring in accordance  
with a result of said comparison.

10 8. A computer readable medium containing the computer  
program claimed in claim 7.

09872955-060401